

BIS 2S Clamps with Lining (M8,M8/10)

For metal pipes Ø 12 - 220 mm

Features and Benefits:

- Two-screw clamp
- Screws secured with anti-loss washer
- Also available with Triplo-nut
- Lining resistant to ageing

Material:

Steel, noise insulating lining to DIN 4109, EPDM rubber

Surface finish : Electro zinc plated. Steel Profile (B X S)



Part No.	D inch	D mm	DN mm	B mm	H mm	h mm	b x s mm	Fa, z (N)	RAL ¹	Pack 1
334 3 019	-	15-19	10	58	44	29	20 x 1,25	220	RAL ¹	50
334 3 023	1/2"	20-23	15	63	49	32	20 x 1,25	220	RAL ¹	50
334 3 030	3/4"	25-28	20	68	54	34	20 x 1,25	220	RAL ¹	50
334 3 038	1"	32-35	25	75	61	38	20 x 1,25	220	RAL ¹	50
334 3 043	1-1/4"	38-43	32	83	69	41	20 x 1,25	220	RAL ¹	50
334 3 049	1-1/2"	44-49	40	96	78	45	20 x 1,25	220	RAL ¹	50
334 3 056	-	50-56	-	97	84	49	20 x 1,50	220	RAL ¹	50
334 3 063	2"	57-63	50	102	88	51	20 x 1,50	220	RAL ¹	50
334 3 054	-	63-67	-	109	94	54	20 x 1,50	220	RAL ¹	50
334 3 071	-	70-73	-	117	104	59	20 x 1,50	220	RAL ¹	50
334 3 078	2-1/2"	74-80	65	122	108	61	20 x 1,50	220	RAL ¹	50
334 3 086	-	81-86	-	129	116	65	20 x 2,00	430	RAL ¹	50
334 3 092	3"	83-91	80	136	122	68	20 x 2,00	430	RAL ¹	50
334 3 106	-	101-106	-	152	135	74	23 x 2,00	750	RAL ¹	50
334 3 116	4"	106-114	100	157	144	79	23 x 2,00	750	RAL ¹	25
334 3 130	-	125-112	-	176	162	88	23 x 2,00	750	RAL ¹	25
334 3 135	-	131-135	-	178	165	90	23 x 2,00	750	RAL ¹	25
334 3 141	5"	136-139	182	182	168	91	23 x 2,00	750	RAL ¹	25
334 3 168	6"	159-168	150	232	202	107	20 x 3,00	1,220	RAL ¹	15
334 3 200	-	193-200	-	268	238	125	20 x 3,00	1,220	RAL ¹	15
334 3 212	6"	210-212	-	275	243	128	25 x 3,00	1,220	RAL ¹	15
334 3 220	8"	216-220	200	283	251	132	25 x 3,00	1,220	RAL ¹	15

