

## R-DPK paper collated nails with fuel cells

Smooth shank bright nails for timber framing, roofing and other timber applications



### Certificate



## Product information

### Features and benefits

- 34° angle collation with a clipped head ensures the nail is compatible with all leading manufactures tools
- Special coating at the base of the shank improves the drive of the nail and ensures a secure fixing
- Diamond point prevents the timber from splitting
- Waxed paper collation avoids deterioration in wet conditions
- Paper tape collation ensures that no collating material is left on the work site
- Depending on the quantity of nails box contains 1,2 or 3 fuel cells
- A wide variety of combinations of nail coatings and finishes allows everyone to find the right solution for a particular application

### Corresponding products

- R-RAWL-WW90CH Gas powered framing nailer

### Applications

- Timber frame stud work in timber framing industry
- Installation of battens and sheathing in roof construction
- Installation of soffits and other roof finishing elements
- Installation of wooden facades
- Installation of timber flooring and terraces
- Manufacturing of timber standardised structure like Timber frame houses or roof elements

### Base materials

- Timber
- Plywood
- Chipboard
- Wood

### Attention



## Technical Data

Index	Fastener diameter	Length	Head type	Shank type	Finish	Collation method	Protection	Fasteners per	Carton quantity	Fuel cells per	Box weight	Outer weight	EAN
	[mm]	[mm]						[pcs]	[pcs]	[pcs]	kg	kg	
R-DPK-2851	2.8	51	Clipped head	Smooth	Bright	34° paper collated	Minimum 10m	44	3300	3	9.56	9.56	5906675 225616
R-DPK-2863	2.8	63	Clipped head	Smooth	Bright	34° paper collated	Minimum 10m	44	3300	3	11.47	11.47	5906675 047546
R-DPK-3163	3.1	63	Clipped head	Smooth	Bright	34° paper collated	Minimum 10m	44	3300	3	13.25	13.25	5906675 070957
R-DPK-2870	2.8	70	Clipped head	Smooth	Bright	34° paper collated	Minimum 10m	44	3300	3	12.48	12.48	5906675 266749
R-DPK-2875	2.8	75	Clipped head	Smooth	Bright	34° paper collated	Minimum 10m	44	3300	3	13.20	13.20	5906675 225630
R-DPK-3175	3.1	75	Clipped head	Smooth	Bright	34° paper collated	Minimum 10m	44	2200	2	10.34	10.34	4008940 127401
R-DPK-3190	3.1	90	Clipped head	Smooth	Bright	34° paper collated	Minimum 10m	44	2200	2	12.38	12.38	5906675 225654